

## MV-CE200-10GM/GC 20MP, 1" CMOS, GigE Camera

**GigE**  
VISION



The Hikvision MV-CE200-10GM/GC 20 MP 1" CMOS GigE Camera is a high quality device that can be used in a variety of applications, including electronic semiconductor fabrication, factory automation, quality inspection.


### Key Features

- Gigabit Ethernet interface providing 1Gbps bandwidth; Transmitting distance can be 100m without relaying.
- 128MB on-board buffer, for image burst transmitting and retransmitting.
- Support auto exposure control, LUT and Gamma correction.
- Cameras can be synchronized with hard trigger and soft trigger.
- Different exposure modes can be used to capture image.
- Compliant with GigE Vision V1.2, can be supported by third party software.


### Application Scenarios

- Electronic semiconductor
- Factory automation
- Quality Inspection

### Spectral Response



MV-CE200-10GM Quantum Efficiency



MV-CE200-10GC Quantum Efficiency

### Order Model

Mono: MV-CE200-10GM

Color: MV-CE200-10GC



## Specifications

Model	MV-CE200-10GM	MV-CE200-10GC
Parameters	20MP, 1" CMOS, GigE Camera	
<b>Camera</b>		
Sensor	IMX183	
Pixel Size	2.4μm×2.4μm	
Sensor Size	1"	
Resolution	5472×3648	
Frame Rate	6fps	
Dynamic Range	65dB	
SNR	40dB	
Gain Range	0-20dB	
Exposure Time	46μs-2.5sec	46μs-10sec
Shutter Mode	Rolling Shutter. Auto-Exposure, Manual Exposure, One-key Exposure	
Data Interface	Gigabit Ethernet	
General Purpose I/O	Opto-isolated input x1, Opto-isolated output x1, Bi-directional non-isolated I/O x1	
Image Buffer	128MB	
Data Format	Mono 8/10/10p/12/12p	Mono 8/10/10p/12/12p Bayer GB 8/10/10p/12/12p
<b>General</b>		
Power	Approx. 3.45W@12VDC, Voltage 5~15VDC, PoE supported	
Temperature	Working Temperature 0~50°C, Storage Temperature -30~70°C	
Dimension	44mm×29mm×60mm	
Weight	Approx. 68g	
Lens Interface	C-Mount	
Software	MVS or Third-Party Software supporting GigE Vision Protocol	
Operating System	Windows XP/7/10 32/64bits	
Compliance	GigE Vision	
Certification	CE, FCC, RoHS	

### Recommended Accessories

- **Power:** 12VDC @1A power adapter
- **NIC:** Intel Pro1000 and above version recommended
- **Network Cable:** CAT5e or CAT6 network cable recommended

### Dimensions

